

FIRECHIEF LITH-EX EXTINGUISHERS

FIRECHIEF®
making the world a safer place

LITHIUM-ION

BATTERY SAFETY RANGE

MODEL:

FLE1 FLE6

FLE2 FLE9



- Designed for use on Lithium-ion battery fires
- BSI Kitemarked to EN3 and MED approved (Models FLE2, FLE6, FLE9)
- Can extinguish Lithium-ion battery fires, uncontrollable by other extinguisher types
- Quickly cools and prevents excessive heat, forming a thermal barrier to stop fire propagation
- Easy to store
- Non-toxic
- Environmentally friendly
- Ideal for use on mobile phones, laptops, tablets, power tools, toys, electric scooters and e-bikes
- 5 year guarantee



KM 614276
BS EN 3

0029



+44 (0) 330 999 0019



sales@firechiefglobal.com



firechiefglobal.com

LITHIUM-ION

BATTERY SAFETY RANGE

FIRECHIEF®

making the world a safer place

FIRECHIEF LITH-EX EXTINGUISHERS

A lithium-ion battery fire may result from physical damage that causes a short circuit, overcharging or by increased external temperature.

Firechief Lith-Ex is the world's first fire extinguisher designed to tackle Lithium-ion battery fires in mobile phones, tablets, laptops, toys, power tools and electric scooters.

The Firechief Lith-Ex range also includes Battery Fire Blankets, Fire Suppression Kit Bags and Fire Resistant Containers. Please contact us for details.

MODEL:

FLE1 FLE6
FLE2 FLE9



Specifications

| Model | FLE1 | FLE2 | FLE6 | FLE9 |
|--------------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Product Code | 100-1576 | 100-1577 | 100-1578 | 100-1579 |
| Description | Firechief 1L Lith-Ex Extinguisher | Firechief 2L Lith-Ex Extinguisher | Firechief 6L Lith-Ex Extinguisher | Firechief 9L Lith-Ex Extinguisher |
| Battery Capability Suitability (Wh)* | 60-100 | 100-250 | 250-500 | 500-750 |
| Capacity (ltr) | 1 | 2 | 6 | 9 |
| Fire Rating | 3A | 5A | 13A | 13A |
| MED Approval | N/A | YES | YES | YES |
| Throw Range (m) | 1.5 - 2.0 | 1.5 - 2.0 | 1.5 - 2.0 | 1.5 - 2.0 |
| Discharge Time (secs) | 25 | 50 | 120 | 180 |
| Working Pressure (bar) | 15 | 15 | 15 | 15 |
| Temperature Range (°C) | +5/+60 | +5/+60 | +5/+60 | +5/+60 |
| Product Height (mm) | 350 | 410 | 530 | 672 |
| Product Diameter (mm) | 85 | 110 | 170 | 170 |
| Filled Weight (kg)** | 2.1 | 3.9 | 10.7 | 15.0 |
| Carton Height (mm) | 360 | 420 | 525 | 670 |
| Carton Length (mm) | 102 | 125 | 197 | 199 |
| Carton Width (mm) | 104 | 128 | 267 | 226 |
| Packaged Weight (kg)*** | 2.5 | 4.0 | 12.0 | 16.0 |
| Product EAN | 5055377960544 | 5055377960551 | 5055377960568 | 5055377960575 |

* Guide only.

** Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging.

*** Includes all packaging, hose / horn and bracket.

For more information contact: Firechief Global, 3 Lands End Way, Oakham, Rutland, UK, LE15 6RB | Imported into EU by: Sentura Group (Ireland) Ltd, Joyce House, 21-23 Holles Street, Dublin 2, Ireland



+44 (0) 330 999 0019



sales@firechiefglobal.com



firechiefglobal.com